

**Standard System includes:**

- Fitted Carrying Case
- User Manual



The HI-1501 is Holaday's most popular Microwave Oven Leakage Meter.

The device provides accuracy and portability for widespread use by oven manufacturers, service technicians, regulatory agencies and public health officials.

It is virtually immune to failure caused by excessive fields. Three ranges are available for increased resolution in leakage measurement.

**Specifications**

Frequency Response  
Ranges  
Response Time

Maximum Power Density  
Power Supply  
Dimensions  
(3.5" x 6" x 2.5")  
Probe Length  
Probe Cable Length

**Standard Accessories**

Fitted Carrying Case  
User Manual

2450 MHz  
0-2, 0-10, 0-100 mW/cm<sup>2</sup>  
Fast Mode: 1sec  
Slow Mode: 2.5 secs (to 90% of Impulse Level)  
2 W/cm<sup>2</sup>  
2 ea. 9V Alkaline Batteries  
8.9 W x 15.3 H x 6.4 D cm  
30cm (12")  
1.2m (4')

**USA**

Tel +1.512.531.6400  
Fax +1.512.531.6500

**Finland**

Tel +358.2.8383.300  
Fax +358.2.8651.233

**UK**

Tel +44.1438.730.700  
Fax +44.1438.730.751

**France**

Tel +33.1.48.65.34.03  
Fax +33.1.48.65.43.69

**China**

Tel +8610.8275.5086  
Fax +8610.8275.5537

**Japan**

Tel +81.3.3813.7100  
Fax +81.3.3813.8068