

## PROBE INTERFACE HI-4413P Fiber to Serial Converter

ETS-Lindgren's HI-4413P Fiber to Serial Converter is an economical way to collect and display data from all of the ETS-Lindgren EMC optically coupled field probes.



ETS-Lindgren's HI-4413P Fiber to Serial Converter is an economical way to collect and display data from all of the ETS-Lindgren EMC optically coupled field probes. Connecting to the Serial port of a personal computer, the HI-4413P provides the interface with power directly from the serial port, so no external power supply is required.

ProbeView™ LT software (available for download from our website) provides a simple tool for collecting data and storing the field values on a personal computer.

ProbeView II is available at additional cost and provides real-time display, logging and analysis functions of EMF data. It can display a variety of test information, both numerically and graphically. A field intensity versus time graph is on the main screen along with the maximum field, X, Y, Z, and RMS values in addition to a variety of data logging options.

### Key Features

- Fiber Optic Modem
- Attaches to PC Serial Port
- Operational With ETS-Lindgren Battery Powered Probes
- No External Power Supply
- ProbeView LT Available for Download
- Fully Compatible with ProbeView II Software (Sold Separately)

### Specifications

#### Electrical Specifications

Optical Connectors: FSMA (2)  
RS-232 Interface: DB9

#### Physical Specifications

Length: 5 cm (2.0 in)  
Width: 2.8 cm (1.1 in)  
Thickness: 1.27 cm (0.5 in)

#### Other Specifications

- HI-4413P Fiber to Serial Converter
- Downloadable ProbeView LT Software

Product Charts



HI-4413P Fiber to Serial Converter


Computer  
Serial or USB Port

ProbeView LT software  
available free from our  
website

**HI-6022/HI-6023** Field Probe, 10 kHz - 1 GHz, 2.0 - 800 V/m



**HI-6005/HI-6006** Field Probe, 100 kHz - 6 GHz, 0.5 - 800 V/m



**HI-6053** Field Probe, 10 MHz - 40 GHz, 2.0 - 800 V/m

