

LOOPS 6512 Shielded Loop Antenna

ETS-Lindgren's Model 6512 has a frequency range of 9 kHz - 30 MHz and is a passive loop antenna designed for both emissions and immunity tests.



ETS-Lindgren's Model 6512 has a frequency range of 9 kHz - 30 MHz and is a passive loop antenna designed for both emissions and immunity tests. Every loop antenna can be individually calibrated in accordance with the IEEE-291 Section 2.3.1 methods, using NIST traceable equipment. By knowing the actual antenna factors and performance characteristics of an antenna instead of typical data, you can more accurately measure field strength in your tests.

Key Features

- Frequency range: 9 kHz - 30 MHz
- Individually Calibrated Two Year Warranty

Specifications

Electrical Specifications

Frequency Minimum: 9 kHz
Frequency Maximum: 30 MHz
Connectors: BNC (f)
Maximum Input Power: 20 W
Pattern Type: Omnidirectional
Polarization: Linear

Physical Specifications

Height: 59.8 cm (23.54 in)
Length: 3.8 cm (1.50 in)
Width: 12.7 cm (5.00 in)
Weight: 1.6 kg (3.53 lb)

Other Specifications

- Loop Antenna
- Mounting Bracket drilled accepts ETS-Lindgren or other tripod mount with standard

Product Charts

6512
Magnetic and
Electric
Antenna Factors

