



PRODUCT BROCHURE

ADIVIC
— RF TEST & MEASUREMENT —

MP7300 Features

1. Adjustable bandwidth from 1 MHz to 45 MHz
2. Frequency coverage from 300 KHz to 3.0 GHz
3. Active and passive RF input port
4. 250 MS/s sampling rate in recording and playback path respectively
5. 16-bit resolution for Rx and 14-bit for Tx
6. 2 channels with 22.5 MHz recording and playback
7. Diversity receiver and generator
8. In support of GPS NMEA data logging recording
9. Remote control available
10. Pre-trigger recording function
11. Data formats compatible to MATLAB analyzer
12. Software utility support including I/Q data extractor and File segment



MP7300 3.0 GHz RF Signal Analyzer Specifications

Frequency

Frequency range : 300 KHz to 3.0 GHz
Continuous bandwidth : 45 MHz
Frequency resolution : 1 KHz / step minimum
Resolution bandwidth (RBW) : Fully adjustable (100 Hz to 3 MHz)
Warm-up time (typical) : 30 minutes
Temperature stability : ± 20 ppb maximum
Initial achievable accuracy : ± 50 ppb maximum

Aging

Per year : ± 100 ppb maximum
Per day : ± 1 ppb maximum
Initial achievable accuracy : ± 50 ppb maximum

Spectral purity

Phase Noise @ 1 KHz offset, 1 GHz : < -80 dBc/Hz
RF input Spurious Response : < -90 dBm

Noise Density

Passive Port (Gain : 40 dB / 100 MHz) : < -165 dBm/Hz
Active Port (Gain : 20 dB / 100 MHz) : < -145 dBm/Hz

Amplitude(Passive Port)

Input level accuracy (15 to 35 °C) : ± 1 dB
Input signal range @ CW mode : -145 dBm to -30 dBm
VSWR @ 40 dB Gain : < 2.5
Gain Range : 0 to +40 dB @ 5 dB step
Input level resolution : 0.01 dB
Maximum DC input : ± 50 VDC
Group delay variation : 30 ns Typical

Amplitude (Active Port)

Input level accuracy (15 to 35 °C) : ± 1 dB
Input signal range @ CW mode : -135 dBm to +10 dBm
VSWR @ 25 dB : < 2.5
Gain Range : -5 to +20 dB @ 5 dB step
Input level resolution : 0.01 dB
DC Voltage Output Range : 0 to +10 V @ 0.1 V / step
Group delay variation : 30 ns Typical

RF input

Passive RF input : 50 Ω , AC-coupled N female
Active RF input : 50 Ω , DC-coupled N female

IF Band

Resolution : 16-bit
Sample rate : 250 MS/s

Storage

Storage : SSD 300 GB X 4

Calibration

Calibration : 1 year

Environment

Operating temperature : 0 to +50 °C
Relative humidity : 10 to 90%
Storage temperature : -20 to 70 °C
Relative humidity : 5 to 95%

Frequency Characteristics

Frequency range : 300 KHz to 3.0 GHz
Real-time bandwidth (Digital vector modulation bandwidth) : 45 MHz maximum
Frequency resolution : 1 KHz / step minimum
Warm-up time (typical) : 30 minutes
Temperature stability : ± 20 ppb maximum
Per year : ± 100 ppb maximum
Per day : ± 1 ppb maximum

Initial achievable accuracy : ± 50 ppb maximum

Spectral purity

Phase Noise @ 1 GHz, 1KHz offset : < -80 dBc/Hz

Spurious Responses

Second harmonic : < -40 dBc

IMD3

(two -13 dBm tones, > 200 KHz apart) : -70 dBc Typical
LO leakage : < -80 dBm

RF Output Characteristics

Output power range : ≥ 25 MHz : -145 dBm to +5 dBm /
 < 25 MHz : -145 dBm to -10 dBm
Amplitude resolution : 0.1 dB / step minimum
Amplitude Accuracy : $< \pm 1$ dB -100 dBm to -10 dBm /
 $< \pm 2$ dB < -100 dBm
Output Impedance : 50 Ω

Voltage Standing Wave Ratio (VSWR)

25 MHz to 3.0 GHz : < 2.5

MP7300 3.0 GHz RF Signal Generator Specification

Overload protection on RF output

Maximum reverse RF power : 1 Watt maximum
Maximum DC input : ± 25 VDC

Noise Floor @ 1GHz

-10 dBm output power : < -120 dBm/Hz Typical
-20 dBm output power : < -130 dBm/Hz Typical
-30 dBm output power : < -140 dBm/Hz Typical
-40 dBm output power : < -150 dBm/Hz Typical
-50 dBm output power : < -160 dBm/Hz Typical

Flatness

IF Band(20 MHz) flatness : 1 dB Typical
Group delay Variation : 30 ns Typical

RF Output

RF Output : 50 Ω , AC-coupled N female

IF Band

Resolution : 14-bit
Sample rate : 250 MS/s

Calibration

Calibration : 1 year

Operating Environment

Operating temperature : 0 to +50 °C
Relative humidity : 10 to 90%
Storage temperature : -20 to 70 °C
Relative humidity : 5 to 95%

Copyright © 2007 ADIVIC Technology Corporation. All rights reserved.
All company and product names are trademarks or registered trademarks of their respective manufactures.
ADIVIC Technology Corporation reserves the right to change without notice

6F., No.345, Xinhua 2nd Rd., Neihu Dist., Taipei City 114, Taiwan
TEL: +886 2 2791 1718 FAX: +886 2 2791 1887 www.adivic.com

ADIVIC
— RF TEST & MEASUREMENT —