

ASY-AE Series <u>AZ/EL Positio</u>ners

sales@asysol.com



- ▲ ASYSOL's Azimuth over Elevation Positioners are compact, robust and application focused in their design. They are simple to use, allowing for safe and reliable operation from the moment they are operated. All the models are backlash error free, assuring the user of the highest levels of standard accuracy.
- The positioners have user connector interfaces, integrated slip rings (12 channels are available as standard), absolute encoders, RF connectors, rotary joints and internal RF wiring meaning you can depend upon the ASY-AE positioner series to provide highly accurate rotation, upon cross-roller type slewing bearings.
- Fitted with industry standard brushless motors and distributed driver electronics, the user can take advantage of any combination of multiple positioners and slides for bespoke user-concepts of simultaneous real time motion.
- Positioners are supplied with a test and calibration report, as well as user manuals and user documentation helping the end-user make optimal use of the product.





Specifications

| Model Number | ASY-AE-25 | ASY-AE-28 | ASY-AE-35 | ASY-AE-50 | ASY-AE-60 |
|-----------------------------|----------------------------|------------------|------------------|------------------|------------------|
| Maximum payload [Kg] | 50 | 100 | 200 | 1.000 | 3.000 |
| Bending Moment, static [Nm] | 400 | 700 | 1.600 | 1.800 | 5.400 |
| Torque [Nm] AZ / EL | 100 / 200 | 200 / 495 | 420 / 890 | 720 / 1,450 | 1,450 / 3,000 |
| Nominal speed [rpm] AZ / EL | 10 / 10 | 10 / 10 | 10 / 10 | 2/1 | 2/1 |
| Travel [deg] AZ / EL | Continuous / +85 to -40 | Continuous / ±95 | Continuous / ±95 | Continuous / ±95 | Continuous / ±95 |
| Accuracy [deg, RMS] AZ / EL | 0.02 / 0.05 | 0.03 / 0.02 | 0.03 / 0.02 | 0.017 / 0.017 | 0.017 / 0.017 |
| Turntable size [mm] | 250 | 250 | 350 | 500 | 600 |
| Weight [Kg] | 140 | 70 | 100 | 420 | 600 |
| Motor power (W) AZ / EL | 400 / 345 | 440 / 940 | 940 / 1.800 | 600 / 600 | 940 / 940 |

Options:

- High-torque
- High speed
- Rotary joint options for frequencies up to 67 GHz
- Adjustable limit switches
- Wiring options for dual-channel RF feed-through
- High accuracy (0.003 degrees)
- Accuracy calibration under load (set of custom loads)
- Custom wiring and slip rings (additional channels are available upon request)
- Custom energy chain for RF, power, cooling or FO cabling
- Customised turntables

Ver022021

Antenna Systems Solutions S.L. Isabel Torres 9 39011 Santander Cantabria, Spain

- sales@asysol.com
- +34 678 813 413
- @ www.asysol.com



